

REMARKS

By this paper, Applicant has amended claim 1. Applicant has not added any claims. The independent claims remain claims 1, 10, 26, 29 and 33. This amendment contains no new matter. Entry of this amendment is respectfully requested.

Double Patenting

Applicant has filed a terminal disclaimer with this paper.

Claim Rejections – 35 USC § 102***Claims 1 and 4***

The Examiner has rejected 1 and 4, under 35 USC § 102 as being unpatentable over Lucas, U.S. Patent No. 3,822,521 ("Lucas").

Applicant has amended claim 1 to positively claim the connection between the apparatus and the wall.

Allowable Subject Matter

The Applicant would like to thank the Examiner for indicating that claims 22 – 28 and 30 – 32 would be allowable, if written in independent form, and for allowing claims 33-36.

Applicant has not amended these claims at this time. Applicant hopes the Examiner will now consider these claims allowable based on the amendment and arguments raised with respect to claim 1 from which these claims depend.

Conclusion

Applicant believes the claims are currently in condition for allowance and respectfully requests the same.

Please direct any calls in connection with this application to the undersigned at (510) 832-4111.

attachment points attached to said holdown bolts and said upper end of said vertical posts attached to said upper portions of said wall so that said apparatus thereby reduces the tendency of said upper portions of said wall to move relative said foundation as a result of shear stress by transmitting said shear stress from said upper portions of said wall through said vertical members and said at least one panel member to said anchor points and said holdown bolts positioned in said foundation, and wherein said posts and said panel of said apparatus for reducing the tendency of said wall to move are separate members from said studs, said upper plate and said lower plate of said wall.

11. (Previously amended) The apparatus of claim 10, further comprising;

an upper horizontal member that interconnects said upper portions of said two vertical posts, wherein connection between said upper ends of said vertical posts is achieved by connecting said upper horizontal member to said upper ends of said vertical posts; and

a lower horizontal member that interconnects said lower ends of said two vertical posts, and wherein said upper horizontal and said lower horizontal members are separate members from said upper plate and said lower plate of said wall.

12. (Previously amended) The apparatus of Claim 11, wherein said one or more panel members is comprised of two panel members attached to said front and said back side of said two vertical posts and to said upper and lower horizontal members.

13. (Previously amended) The apparatus of Claim 12, wherein said two attachment points are comprised of two brackets that are connected to said holdown bolts in said foundation, wherein said two brackets receive said lower horizontal member and said two vertical posts so that said lower horizontal member and said two posts can be fixedly attached to said brackets.
14. (Previously amended) The apparatus of claim 10, further comprising shear bolts mounted in said foundation and wherein said lower horizontal member is attached to said shear bolts mounted in said foundation to thereby reduce the likelihood of a lower portion of said apparatus becoming dislodged from said foundation in response to lateral forces applied to said wall.
22. (Original) The apparatus of claim 10, where said apparatus is dimensioned so that a gap exists between said apparatus and said upper plate of said wall.
23. (Original) The apparatus of claim 10, wherein said panel of the apparatus is not directly connected to any of the studs, the upper plate or the lower plate of said wall.
24. (Original) The apparatus of claim 10, wherein said apparatus connects to said upper plate of said wall.
25. (Original) The apparatus of claim 11, wherein said panel does not extend beyond said upper horizontal member of said apparatus.

26. (Original) A method of building a wall so that the tendency of an upper portion of a wall having an upper plate to move relative a lower portion of said wall is reduced, said method comprising the steps of:

providing a foundation for said wall, wherein one or more holdown bolts are each installed in said foundation at a pre-selected location in said foundation;

mounting two or more studs so as to extend substantially vertically upward from said foundation;

positioning an upper plate on a top surface of said two or more studs;

attaching a lower portion of a shear reduction panel to said holdown bolts so that said panel is positioned between said two studs, said shear reduction panel being pre-assembled to have two vertical posts, an upper horizontal member and a lower horizontal member connecting said two vertical posts, and at least one panel interconnecting said two vertical posts substantially along the vertical lengths of said posts; and

attaching an upper portion of said shear reduction panel to said upper plate of said wall so that movement of said upper plate of said wall in response to lateral forces applied to said upper plate of said wall in response to lateral forces applied to said wall is reduced as a result of the lateral forces being transmitted through the vertical posts and the interconnecting panel to the holdown bolts mounted in the foundation.

27. (Original) The method of claim 26, wherein said the panel does not extend beyond said upper horizontal member of said apparatus.

28. (Original) The method of claim 26, wherein said pre-assembled shear reduction panel is dimensioned so that a gap exists between said shear reduction panel and said upper plate of said wall.

29. (Original) A method of building a wall so that the tendency of an upper portion of a wall having an upper plate to move relative to a lower portion of said wall is reduced, said method comprising the steps of:
- providing a foundation for said wall, wherein one or more holdown bolts are each installed in said foundation at a pre-selected location in said foundation;
 - mounting two or more studs so to extend substantially vertically upward from said foundation;
 - positioning an upper plate on a top surface of said two or more studs;
 - attaching a lower portion of a shear reduction panel to said holdown bolts so that said panel is positioned between said two studs, said shear reduction panel being pre-assembled to have an upper horizontal member and a lower horizontal member, and at least one panel interconnecting said upper horizontal member and said lower horizontal member; and
 - attaching an upper portion of said shear reduction panel to said upper plate of said wall so that movement of said upper plate of said wall in response to lateral forces applied to said wall is reduced as a result of the lateral forces being transmitted through the vertical posts and the interconnecting panel to the holdown bolts mounted in the foundation.
30. (Original) The method of claim 29, wherein said panel has lips that extend substantially perpendicular to the panel and then substantially parallel to the panel.
31. (Original) The method of claim 30, wherein said upper and lower horizontal members are U-shaped.

32. (Original) The method of claim 31, wherein said shear reduction panel further comprises thick plates connected to said shear reduction panel where said shear reduction panel connects to said holdown bolts.

33. (Original) An apparatus for reducing the tendency of an upper portion of a wall in a building to move with respect to a foundation as a result of lateral forces applied in a direction parallel to the wall, said apparatus in combination with said wall comprising:

said wall, said wall having an upper plate, a lower plate, and studs connecting said upper plate to said lower plate, said studs supporting said upper plate;

said apparatus inserted within and connected to said wall, said apparatus comprising

upper and lower horizontal members, wherein said upper and lower horizontal members are positioned in a pre-selected spaced relationship;

at least one panel member interconnecting said upper and lower horizontal members; and

two holdown bolts that are anchored in a foundation of said wall, wherein said apparatus is attached to said two holdown bolts and wherein said apparatus is connected to said wall by said upper horizontal member attached to said upper portions of said wall so that said apparatus thereby reduces the tendency of said upper portion of said wall to move relative said foundation as a result of shear stress by transmitting said shear stress from said upper portion of said wall through said at least one panel member to said holdown bolts positioned in said foundation, and wherein said upper and said lower horizontal members and said panel of said apparatus for reducing the tendency of said wall to move are separate members from said studs, said upper plate and said lower plate of said wall.

34. (Original) The method of claim 33, wherein said panel has lips that extend substantially perpendicular to the panel and then substantially parallel to the panel.
35. (Original) The method of claim 34, wherein said upper and lower horizontal members are U-shaped.
36. (Original) The method of claim 35, wherein said apparatus further comprises thick plates connected to said shear reduction panel where said shear reduction panel connects to said holdown bolts.

PATENT

Attorney Docket No. SST/1070
SN:09/603,727; Filed June 23, 2000

Respectfully submitted,

A handwritten signature in black ink, appearing to read 'Charles R. Cypher', is written over a horizontal line.

Charles R. Cypher
Law Offices of James R. Cypher
405 14th Street
Suite 1607
Oakland, CA 94612

Date: September 11, 2008

Reg. No.: 41,694

Tel. No.: 510-832-4111

Fax No.: 510-832-4115

Customer No.: 498

Enclosures: Terminal Disclaimer (1 page)
Credit Card Authorization Form (1 page)
Return Receipt Post Card.